

CONFIDENTIAL

25X1

December 4, 1961

*file:
Mod 2 Enc.*

Dear Sir:

Enclosed are the copies of the "advertising" pieces for the Models 1, 2, and 3 Air-Fed Incinerators that you left with us for our comments. Glen and I have reviewed these and have suggested some changes, which are indicated in pencil on the enclosed.

If you have any questions about our suggested changes, please do not hesitate to call.

Sincerely,

25X1

ABW:mlm

In Duplicate

Enclosures

ORIGINAL CL BY

☒ DECL ☒ REVW ON

EXT BYND 6 YRS BY

REASON

235979

2010

SPR 16

3d(3)

58

086

22^M

020780

52

2

2010

010956

61

<

CONFIDENTIAL

*file.
Mod 2 Inc.*

MODEL 2 AIR-FED INCINERATOR

The Model 2 Air-Fed Incinerator is provided for those facilities requiring an intermediate emergency destruction of classified documents at a maximum rate. Additionally this unit may be used for daily or weekly scheduled burn periods which will provide a maximum security capability not heretofore available. The incinerator will destroy all paper or paper products including film, negatives and those products of combustible nature manufactured of cellulose base materials. Given below is the technical data characteristics and requirements for the installation and operation of this incinerator.

Technical Data

85-120
Capacity: ~~150~~ 200 pounds of material per hour.

Electrical Requirement: 1 or 3 phase, 60 or 50 cycle, 115/230 for single phase operation, or 208, 220/440 3 phase operation.

Space Requirement: Physical: 9 square feet. Functional: approximately 25 square feet. Minimum ceiling 8 feet 6 inches. Shipped in three pieces for individual facility assembly. Common tools are required for assembly and 2 to 3 personnel available to assist in lifting and handling.

Description: The incinerator assembled weighs approximately 600 pounds, has a diameter of 24 inches and an assembled height of 79 inches. The exhaust stack configuration (to be built at facility) is welded, stainless steel construction having a minimum cross section area of 62.8 square inches.

Stock Order Number

3/4540-H.O.-6016